

OPERATING INSTRUCTIONS

Caution! Do not open water hose shut-off with other valves closed! This may exert too much pressure and may damage reverse flush valve and void any warranty. Do not lean on the Flush King valve after attaching it to the sewer drain.

Please follow instructions below:

1. Remove RV drain cap and attach reverse flush valve (clear end) to the RV's sewer connection.
2. Attach sewer hose to the reverse flush valve.
3. Connect water supply hose to water hose shut-off. Make sure valve is closed.
4. Open Flush King valve and Black Tank dump valve to drain the black holding tank. When black tank is empty, close Flush King valve. Turn on water (at water hose shut-off valve).
5. Refill holding tank to desired level. Turn water off (at water hose shut-off valve) and reopen Flush King valve, to drain tank. Repeat steps 4 and 5 until discharge water is clean.
6. Close Black Tank dump valve and open Gray Tank dump valve to drain gray holding tank. When drained, close Flush King valve and turn on water (water hose shut-off valve) to refill holding tank to desired level.
7. Turn water off (at water hose shut-off valve) and reopen Flush King valve to drain tank. Repeat steps 6 and 7 until discharge water is clean.
8. With both tanks flushed, close Gray Tank dump valve and turn on water (water hose shut-off valve) to wash out sewer drain hose.

Always use a green or gray hose (not white) when connecting to the Flush King. A backflow preventer has been installed into the water-hose fitting.

Note: This is not a permanent installation. Remove Flush King when you are finished.



Valterra Products, Inc.
15230 S.F. Mission Blvd. #107
Mission Hills, CA 91345
www.valterra.com

Lift
to Open

Caution: Never leave RV unattended when refilling holding tank as overfilling may occur. Periodically turn off flow of water and check level of holding tank to assure overfilling does not occur.